



Hannah 2903



BARGE: HANNAH 2903
LENGTH: 264'-0"
DEADWEIGHT: 2768 LT
LOADED DRAFT: 10-3/4"

CAPACITY: 16,826 BBLs
BREADTH: 52'-6"
NET TONNAGE: 1698 LT
EMPTY DRAFT: Approximately 3'

OFFICIAL #: 289860
DEPTH: 12'-6"
GROSS TONNAGE: 1698 LT

NUMBER OF TANKS:

Cargo Tanks - Five (5) Center1-5

1 - 3,250 Bbls 2 - 3,403 Bbls 3 - 3,406 Bbls 4 - 3,400 Bbls 5 - 3,367 Bbls

Wing Tanks - Ten (10) Port & Starboard

1 - 1,174 Bbls	1 - 1,188 Bbls
2 - 1,184 Bbls	2 - 1,189 Bbls
3 - 1,193 Bbls	3 - 1,193 Bbls
4 - 1,193 Bbls	4 - 1,195 Bbls
5 - 1,205 Bbls	5 - 1,199 Bbls

Bow Rake - One (1) @ 1,517 Bbls Stern Void - One (1) @ 950 Bbls Fuel Tank - One (1) @ 500 Gals.

PUMPING CAPACITY: Two (2) pumps each rated at 1700 BBLs/Hr. (1190 GPM)

LOADING STATIONS: Two (3) stations (midship and aft) with hose derricks
One (1) cross-header location

CERTIFICATIONS: A.B.S. - Maltese Cross A1 Oil Barge with a Great Lakes and Limited Coastwise Load Line Certificate
U.S.C.G. - Subchapter "D" - Grade "D" and "E"
D.O.T. - Certificate of Financial Responsibility

SERVICE: Residual petroleum products and asphalt. Presently serving the Great lakes region. Designed and equipped to transit restricted rivers and harbors. Ideal for bunkering operations.

HULL TYPE: Steel Type III
Double Hulled
Ice Strengthened
Double Raked
Fixed Skegs

BUILT: 1962 - Port Houston Iron Works
Houston, Texas

EQUIPMENT

CARGO PUMPS: Two (2) Worthington Screw Type Pumps driven by a GM 6-71
HEATING COILS: 2" Coils; 40:1 Ratio; Shore steam accessible
DECK WINCH: One (1) Beebe Winch located on stern
ANCHOR: Danforth 750 Lbs. with Beebe Anchor Winch

VESSEL INSPECTION LOCATION: CHICAGO HARBOR
CONTACT PERSON: ED HOGAN – 630-399-0289